

HDS2000 %100 ELECTRICAL ROAD SWEEPER MACHINE



SPONGE %100 ELECTRICAL ROAD SWEEPER MACHINE



TECHNICAL SPECIFICATIONS

Hopper Capacity	2 m3
Payload Capacity	1.5 Tons
Water Tank	400 lt
Engine	72 kW
Type	AC
Battery Type	Lithium
Max. Slope	24%
Operation Type	100% Electrical
Side Brush Diameter	400 mm
Suction Nozzle Diameter	200 mm
Suction Nozzle Wheel Diameter	120 mm
Suction Nozzle Width	810 mm
Suction Width	2000 – 2850 mm
Tyres	225 / 70 R 15 C
Wheelbase	1850 mm
Discharging Height	1700 mm
Discharging Angle	85o ± 5o
Watering Nozzle Pump Output	5 lt / 58 bar (electrical pump)
Sweeping Speed	10 km/h
Cruising Speed	24 km/h
Gradeability	25%
Fan	8000 m3/h
Operational RPM	0 – 3000 RPM

TECHNICAL SPECIFICATIONS

Hopper Capacity	1 m3
Payload Capacity	500 lt
Water Tank	200 lt
Engine	48 kW
Type	AC
Battery Type	Lithium
Max. Slope	24%
Operation Type	100% Electrical
Side Brush Diameter	300 mm
Suction Nozzle Diameter	200 mm
Suction Nozzle Wheel Diameter	120 mm
Suction Nozzle Width	810 mm
Suction Width	1300 mm
Tyres	155 65 R13
Wheelbase	1050 mm
Discharging Height	1600 mm
Discharging Angle	85o ± 5o
Watering Nozzle Pump Output	5 lt / 58 bar (electrical pump)
Sweeping Speed	10 km/h
Cruising Speed	24 km/h
Gradeability	25%
Fan	4000 m3/h
Operational RPM	0 – 3000 RPM